

(19) 世界知的所有権機関
国際事務局



(43) 国際公開日
2000年12月7日 (07.12.2000)

PCT

(10) 国際公開番号
WO 00/74052 A1

(51) 国際特許分類: G11B 19/12, 19/28

(21) 国際出願番号: PCT/JP00/03430

(22) 国際出願日: 2000年5月26日 (26.05.2000)

(25) 国際出願の言語: 日本語

(26) 国際公開の言語: 日本語

(30) 優先権データ:
特願平11/147936 1999年5月27日 (27.05.1999) JP

(71) 出願人 (米国を除く全ての指定国について): 松下電
器産業株式会社 (MATSUSHITA ELECTRIC INDUS-
TRIAL CO., LTD.) [JP/JP]; 〒571-8501 大阪府門真市
大字門真1006番地 Osaka (JP).

(KIMURA, Naohiro) [JP/JP]; 〒611-0021 京都府宇治
市宇治式番92 Kyoto (JP). 渡邊克也 (WATANABE,
Katsuya) [JP/JP]; 〒631-0033 奈良県奈良市あやめ池南
7-854-2 Nara (JP). 石橋広通 (ISHIBASHI, Hiromichi)
[JP/JP]; 〒567-0876 大阪府茨木市天王二丁目6-H-503
Osaka (JP).

(74) 代理人: 山本秀策 (YAMAMOTO, Shusaku); 〒540-
6015 大阪府大阪市中央区城見一丁目2番27号 クリス
タルタワー15階 Osaka (JP).

(81) 指定国 (国内): AE, AG, AL, AM, AT, AU, AZ, BA, BB,
BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM,
DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,
LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL,
PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ,
UA, UG, US, UZ, VN, YU, ZA, ZW.

(72) 発明者; および


(75) 発明者/出願人 (米国についてのみ): 木村直浩

(84) 指定国 (広域): ARIPO 特許 (GH, GM, KE, LS, MW,
MZ, SD, SL, SZ, TZ, UG, ZW), ユーラシア特許 (AM,

[続葉有]

(54) Title: INFORMATION REPRODUCING APPARATUS, INFORMATION CARRIER, AND INFORMATION RECORDING APPARATUS

(54) 発明の名称: 情報再生装置、情報担体及び情報記録装置



7...TR DRIVE
6...TR DRIVE
5...FO DRIVE
8...CONTROL CIRCUIT
11...DATA SLICER
10...SPINDLE DRIVE CIRCUIT
12...PLL CIRCUIT
9...SPINDLE CONTROL CIRCUIT
14...SYSTEM CONTROLLER
13...DEMODULATING CIRCUIT
15...HOST PC

(57) Abstract: An information reproducing apparatus comprises a rotation section (2) for rotating a disk-like information carrier (1) where continuous information in units readable continuously is recorded, a CLV control section (9) for controlling the rotation section so that the information carrier rotates at a constant linear velocity, a CAV control section (9) for controlling the rotation section so that the information carrier rotates at a constant angular velocity, a rotation control selecting section (14) for selectively operating the CLV control section or the CAV control section, and an information identifying section (14) for measuring the information length of the continuous information. The rotation control selecting section selectively operates the CLV control section or the CAV control section according to the result of the measurement of the information length. The information reproducing apparatus reproduces information under suitable rotation drive control according to the size of the continuous information. As a result, the access performance is improved, and the rotational speed of the spindle motor need not be increased more than necessary. Therefore the rotation noise of the spindle motor and the vibration of the reproducing apparatus are reduced.

[続葉有]

WO 00/74052 A1